



Headquarters: Taipei. Taiwan

INDUSTRIES SERVED



\$8.83B CAP

HONORS & AWARDS

- No.5 in Best Taiwan Global Brands
- No.17 in Top 50 Global Automation Vendors
- No.9 in Top 100 Industrial IoT Companies
- Red Dot Product Design Award
- iF Product Design Award

Interbrand










WORLD'S LARGEST IPC COMPANY



Source: OMDIA - Market Share estimates for Industrial PCs: World 2022 Edition

\$2.31B



KEY ECO-SYSTEM PARTNERS













and more

QUALITY SYSTEMS IN PLACE

- ISO9001
- ISO27001
- WFFF SONY GP

- ISO14001 ISO13485
- ISO45001 - TL9000
- REACH

- ISO17025
- RoHS

1.8 MILLION+ sq. ft.

MANUFACTURING PLANTS

Linkou. Taiwan





- 8 SMT lines
- Engineering sample services
- Complex product lines
- Flexible & guick production
- 11 SMT lines
- Chassis design & production
- Mature product lines

Kunshan, China

Cost-effective production



Nogata, Japan

- 4 SMT lines
- Japan design center, CTOS service, logistics center, repair center

WORLDWIDE OFFICES



Manufacturing On-site service Design centers 11 CTOS centers 16 Repair centers 17 Logistics centers 20

More than 90 offices globally!





Table of Content

Pathways to Future Trends & Opportunities in Green Energy	3
Renewable Energy (Solar/Wind)	5
Embracing Digitalization: The Future of Renewable Energy Management	
Renewable Energy Generation Business Eco-System	
 Solar Photovoltaics (PV) Monitoring Application Diagram 	
Case Study Cost-Effective, Scalable, Smart Energy Management Systems	
Battery Energy Storage System (BESS)	9
Mastering Energy Storage in the Renewable Energy Era	
Battery Energy Storage System Eco-system	
All-in-One BESS Application Diagram	
Grid-Scale BESS Application Diagram	
Behind-the-Meter BESS Application Diagram	
 Case Study Building a Connected IoT Infrastructure to Achieve BESS efficiency 	
EV Battery Factory	
 Innovating EV Battery Production through Advanced Automation and AI 	
EV Battery Manufacturing Business Eco-system	
Smart Maintenance & Quality Control in EV Battery Manufacturing	
 Case Study Improving Quality Assurance with Advanced AOI Solution in EV Battery Production Line 	
EV Charging Station ————————————————————————————————————	
The Expansion of EV Charging Stations and Emerging Business Models	
EV Charging Station Business Eco-System	
EV Charging Station Application Diagram	
Case Study Data Collection and Transmission System for Electric Vehicle Charging Points	
Smart Substation	23
The Digital Grid and Substation Virtualization	
Power Grid Business Eco-System	
• IEC 61850 Substation Platform Application Diagram	
 Application Story Smart Substations: Centralized Digital Control for Enhanced Resilience 	
Product Offering Highlight ————————————————————————————————————	27

Pathways to Future Trends & Opportunities in Green Energy

With global trends in green energy, ESG initiatives, and relevant regulations, global renewable energy capacity is expected to reach 4800GW by 2026. According to a Gartner report, this will require businesses to invest heavily in on-site renewable energy generation and storage in order to optimize their long-term energy costs, while contributing to energy security on a larger scale. This is leading energy retailers and energy management companies to investigate and implement behind-the-meter renewable energy generation as well as alternate forms of energy or power augmentation services.

Growing markets in green energy include energy services for on-site generation, energy storage, EV chargers, planning and financing of microgrids, and digital substations. These projects will all require installation, operation, and maintenance. Demand for hybrid energy storage systems in particular is expected to grow with increasing penetration of distributed renewable energy generation, and this will require the development of intelligent energy storage technologies that will make batteries more durable and safer to operate.

Technologies driving this evolution in energy storage include AI, digital twinning, and self-healing materials. Given the massive deployment of IoT sensors that is required to successfully ensure the safe and efficient operation and management of such systems, it is critical that suitable energy storage solutions be developed for the environments in which they operate.

Relevant regulations have already been proposed to help build a circular economy for batteries, such as the 2026 target for European battery passports, which will largely depend on the collection of information pertaining to battery performance and durability. They will also serve as the equivalent of a health record for batteries. Collectively, the shift away from centralized utility-delivered power is both aimed at, and driven by the digitalization, decarbonization, decentralization, and democratization of energy.





Digitalization

Energy digitalization means establishing energy storage solutions that can facilitate the integration of renewable energy into smart, flexible power systems. The effects of digitalization will impact the entire process, from generation and storage, to distribution and consumption. If businesses wish to take control of their energy needs, they will need to deploy real-time AI capable energy systems.

Decarbonization

Advancements in decarbonization will require businesses to re-evaluate their objectives by exploring viable decarbonization pathways and alternative financing options in order to reduce emissions. A key consideration will be for businesses to partner with suppliers who can aid them in achieving energy efficiency targets through the deployment, operation, and management of renewable energy systems.

Decentralization

Decentralization is becoming critical to achieving energy security. It will require significant contribution from businesses, especially larger enterprises, in the adoption of self-generation solutions that will allow them to manage their own energy needs through the construction of micro grids.

Democratization

Energy democratization will continue to involve public effort in the transition toward renewable energy. By enabling independent energy producers and energy trading, the entire sector can be better guided, and be more responsive, by policies and decisions that are made on the basis of localized needs.

Reference



Renewable Energy (Solar/Wind)

As the world's energy landscape shifts, renewable energy sources like solar and wind are becoming increasingly important. Rapid growth in this sector is driving demand for innovative management solutions that optimize energy integration and foster a sustainable future.

According to the International Energy Agency (IEA), renewable capacity will meet 35% of global power generation by 2025.

Embracing Digitalization: The Future of Renewable Energy Management

Addressing the challenges faced by renewable energy generators is crucial to meeting their targets. Traditional IT/OT systems are inadequate for managing the complex and dynamic operations required to scale up renewable energy generation across a diverse energy ecosystem. Thus, emerging technologies that can handle real-time environmental conditions and facilitate more efficient management are critical.


Such technologies build upon existing tools that support remote energy operations. Vendors are now developing modular products with individual APIs that simplify integration into third-party environments. To optimize renewable energy generation and management, a comprehensive toolbox is required, including:

- Big data and predictive analytics: Providing realtime insights for informed decision-making.
- Cloud computing: Enabling connectivity and data exchange across various platforms.
- Modular architecture: Supporting diverse business models and integration with existing systems.
- Intelligent solutions: Collecting data on equipment performance to ensure optimal operation.


As digitalization revolutionizes the renewable energy sector, these technologies will be vital to managing the growing complexity of energy generation and distribution. Hence, these innovations will help renewable energy providers improve efficiency, reduce costs, and contribute to a more sustainable future.

Learn More

Renewable Energy Generation Business Eco-System



Solar Photovoltaics (PV) Monitoring Application Diagram



Case Study | Cost-Effective, Scalable, Smart Energy Management Systems

A reliable Solar Monitoring platform with data collection and transmission to cloud-based monitoring systems, including meteorological sensors, inverters, energy meters, and LV transformers.

Challenges / Requirements:

- Implement green technology for potential project bids to tap into the rising demand for greener and more sustainable buildings.
- Improve sustainability through better energy, environment monitoring, and management.
- Carry out the supply, installation, commissioning, and integration of two 1.5 megawatt-peak (MWp) floating solar PV systems.

Solution:

BBR designed a solution to extract data from meteorological sensors, inverters, and DC combiners and convert it to Transmission Control Protocol (TCP) to safeguard the reliable process of packets. The system uses an energy gateway device to collect Modbus/TCP data from the field. The data is locally stored, then obtained using Advantech's data logger (IPC ESRP-UNO-2484).

Benefits:

- Allows key energy management tasks and maximizing solar power output.
- The use of a web-based platform makes immediate access to data possible.
- Produces enough green energy to supply 30% of the total energy requirements for the installation.



Inverters x 2

| Commission | C

Battery Energy Storage System (BESS)

The world's shift toward renewable energy and decarbonization has made energy storage more crucial than ever before. Ensuring power is delivered reliably, where and when it's needed, is an unprecedented challenge in the renewable energy landscape. Current energy storage systems employ a range of technologies to balance electrical supply and demand, fostering a flexible and sustainable energy infrastructure.

The International Energy Agency predicts that global installed storage capacity will grow by 56% in the next five years, reaching over 270 GW by 2026.


Mastering Energy Storage in the Renewable Energy Era

This rapidly evolving context presents several trends and opportunities, including the growth of distributed renewable energy driven by government promotion of renewables and rising demand for microgrids. Decarbonization initiatives are leading to substantial demand for battery storage systems. Additionally, the digitalization of grids for real-time demand management will involve leveraging IoT technologies such as smart meters, sensors, remote operations and maintenance (O&M), and AI.

However, there are also notable challenges. Aligning renewable energy generation with fluctuating demand and managing the variability of renewable energy sources can be difficult. Addressing the high peak power demand of faster EV charging and superchargers, which is challenging to forecast, is another issue. Ensuring the availability of reliable device vendors and global services to support energy storage is also essential.

Advantech is well-positioned to address these challenges with our comprehensive product portfolios for battery energy storage system (BESS) builders, system integrators, and O&M service providers. Our global logistics, technical support, and services can help customers navigate the future of energy generation with efficient BESS solutions.


Battery Energy Storage System Eco-system




Providers

All-in-One BESS Application Diagram


BESS: Battery Energy Storage System



Grid-Scale BESS Application Diagram



Behind-the-Meter BESS Application Diagram



Case Study | Building a Connected IoT Infrastructure to Achieve BESS Efficiency

Battery Energy Storage Systems (BESS) uses batteries to store excess energy generated by renewable sources such as solar and wind power for later use. With BESS, we can reduce energy loss and make energy distribution more efficient.

Challenges / Requirements:

- HVAC control in BESS requires I/O signals such as analog inputs for temperature data acquisition in the battery rack, and digital output for alarm detection and HVAC control.
- Edge gateways are required to deal with data processing and control, and edge computers serve for overall system management.


Solution:

- Each battery rack has one ADAM-6717 I/O gateway as the HVAC controller that controls the HVAC system. ADAM-6717 contains I/O modules and basic computing functions to deal with the I/O control process and alarm/event handling.
- Each battery bank (several battery racks) uses ECU-150 edge gateways to manage devices (including ADAM-6717) in the battery bank and transmits information to UNO-2271 edge computers.
- UNO-2271 edge computers run the management systems that monitor the equipment status of each battery bank.
- An EKI-2525 unmanaged switch is used to connect Ethernet devices.

Benefits:

- ADAM-6717 Linux I/O gateway with analog and digital I/O modules deals with data collection and handles process control.
- ECU-150 edge gateway is equipped with high performance NXP i.MX 8M processor and serial ports that can collect and manage devices in battery banks.
- UNO-2271 fanless edge computers with industrial-grade design, provide reliable management capabilities for BESS.





According to IEA, in 2021, demand for automotive lithium-ion batteries reached 340 GWh, more than twice the demand in 2020. It is projected that the demand for EV batteries will grow to over 3,500 GWh by 2030. By 2030, battery demand from EVs is expected to increase to between 2.2 and 3.5 TWh, requiring the construction of 52 to 90 additional gigafactories with an annual production capacity of 35 GWh. This growing need for automation technology in gigafactories presents significant opportunities for Industry 4.0 applications.

EV Battery Factory

Lithium-ion batteries, essential for electric vehicles (EVs), use active and sensitive materials. This means that imperfections during production can lead to diminished battery performance, capacity, and lifespan, or even accidents. Because battery production operates on an economy-of-scale basis, any interruptions can cause substantial financial losses. State-of-theart technologies are integrated thus essential to battery manufacturing to guarantee battery quality and equipment availability.

Machine vision systems ensure quality inspection and traceability in production lines. This requires real-time control systems to handle robots and actuators for accurate material management, with smart sensors employed to monitor conditions. Al technology is extensively employed to improve inspection precision and facilitate predictive maintenance.


Innovating EV Battery Production through Advanced Automation and Al

Emerging trends include the extensive application of AI in image analysis and big data analytics, which plays a vital role in machine vision and equipment predictive maintenance. Gigafactories and their equipment suppliers require partners capable of delivering ready-to-use, AI-driven solutions for quality assurance and OEE improvement projects.


Advantech provides cutting-edge edge platforms driven by the latest CPU/GPU computing technologies. Additionally, Advantech actively cultivates robust alliances with co-creation collaborators in AI, real-time control, and intelligent manufacturing. These partnerships are essential for delivering top-of-the-line hardware platforms, devices, and automation resources to battery manufacturers.

Learn More

EV Battery Manufacturing Business Eco-system



Smart Maintenance & Quality Control in EV Battery Manufacturing



Case Study | Improving Quality Assurance with Advanced AOI Solution in EV Battery Production Line

Battery makers are facing a surging demand from electric vehicles and stationary energy storage systems. This is accelerating the creation of new technologies for manufacturing to boost production performance. Vision inspection is one of those important technologies that can meet these requirements. Advantech works on automation projects for gigafactories, which helps create new IPC design opportunities in a virtuous cycle of development.

Challenges / Requirements:

- Overcoming poor quality-inspection performance.
- Overcoming the difficulty of upgrading and expanding.
- Need for reliable HW with long-term support.
- Material and supply chain shortages.


Solution:

- 4U Industrial PC supports 12th Gen. Core[™] i, with shock proof, front accessible drive bays, reinforced cooling solution for harsh environment.
- High-performance GPU card with longevity support for image processing and AI inference – Ouadro RTX-A4000H.
- PoE GigE vision frame grabber card with remote camera power on/off function PCIE-1674.

Benefits:

- CTOS service for flexible configuration to meet different spec requirements of various machines.
- 1Grms vibration, 40°C temp, 10G shock industrial reliability minimizing system down time.
- Remote PoE camera power on/off minimizes maintenance time.
- Global certification service and regional service center support.





EV Charging Station

Demand for electric vehicles (EVs) is growing due to corporate sustainability strategies, government financial incentives, and stringent environmental laws. Consequently, many enterprises are investing in EV charging solutions and entering the EV charging station market. EV charger manufacturers and engineering procurement and construction companies are increasingly installing EV chargers in various locations, providing a wide range of services such as installation, operation, and maintenance of EV charging stations. This enables enterprises to adopt these solutions without significant capital investment.


While home and workplace charging are likely to fulfill a large portion of the overall demand, the number of public chargers still needs to increase significantly to over 15 million units by 2030.

The Expansion of EV Charging Stations and Emerging Business Models


Various business models have emerged globally, offering a range of EV charging station solutions. These models provide a choice of AC/DC charging technologies suitable for residential or fleet use, and different public or private locations. Key factors for charging station service providers include customization capabilities to meet distinct requirements, network reliability to ensure service quality, and integrated services to enable remote monitoring and predictive maintenance.

To meet the increasing need for electric vehicle (EV) charging solutions, Advantech is actively creating groundbreaking products and solutions. Through customizable offerings, reliable network maintenance, and comprehensive services, Advantech empowers customers to develop inventive business models and charging technologies. This enables them to address a wide array of requirements and contribute to a greener, more efficient future for electric transportation.

EV Charging Station Business Eco-System



EV Charging Station Application Diagram



Case Study | Data Collection and Transmission System for Electric Vehicle Charging Points

The charging stations set up by the customer use Advantech solutions for data collection and transmission via charge point protocol (OCPP), which means all data will reliably reach the backend system.

Challenges / Requirements:

- Most large-scale commercial pay-per-use DC charging stations are located outdoors, therefore the charging points must be able to withstand environmental and weather conditions such as dust, precipitation, sustained periods of sunshine, and extreme temperatures.
- Charging stations must be able to transmit data reliably. Information such as charging volume and billing details must be transmitted through OCPP, and functions such as backend system management, remote real-time station monitoring, and energy management must also be integrated.


Solution:

Payment information entered in charging stations by the user is sent to the remote data center via the Advantech ICR-4461 5G cellular router. After the payment is made, data is then transmitted to the charging point controller through the Advantech EKI-2525I industrial unmanaged switch, which sends a signal to turn on the current in the charging station and send power to the connected EV.

Benefits

- Real-time monitoring system significantly improves management efficiency.
- Provides an easy, convenient, and reliable charging experience for EV users.





Smart Substation

The digital grid harnesses connectivity to unite energy consumers and producers, facilitating bidirectional energy transmission. In digital grid investments, the digitalization and virtualization of substations have emerged as crucial elements. These advancements are made possible by the progress in edge computing, edge AI, IT/OT integration, advanced distribution protection, and software-defined assets.




The Digital Grid and Substation Virtualization

Traditional substations rely on copper cables for point-to-point connections, resulting in costly testing and maintenance. Critical assets often lack adequate condition monitoring, leading to information silos and cyclical maintenance strategies. Today's digital substations utilize digital communications, replacing fiber optic networks and copper signal lines. Such secure, high-performance digital infrastructure drives operations and relays asset condition data to cloud-based systems that then leverage predictive algorithms to enhance maintenance effectiveness.


The outcome is reduced maintenance costs, extended asset life, decreased environmental impact, and improved worker safety. This helps utility companies optimize maintenance expenditure, construct substations with smaller footprints, and shorten the time required to build new substations, to deliver reliable, affordable power while generating profit.

The reliability of power system protection, monitoring, control, and asset management has significantly increased from electromechanical relays to modern IEDs. Today's utility information systems utilize standard networking concepts and virtualization, housing multiple systems on a single platform. This reduces the number and variety of devices in substations, saving money and resources while simplifying maintenance. Key to this is virtualization, which is an essential tool for making the grid more sustainable and resilient, thus contributing to the global transition to clean power.

Power Grid Business Eco-System



IEC 61850 Substation Platform Application Diagram



Application Story | Smart Substations: Centralized Digital Control for Enhanced Resilience

Centralized digital substation control simplifies operations by consolidating functions into a single device. Advantech ECU-579, in collaboration with software partners and combined with legacy units, offers a customizable solution for digitalizing substations. This case study explores the benefits and features of the system.

Challenges / Requirements:

- Centralization: The need to centralize protection and control functions into a single device.
- Versatility: Ability to handle a wide range of utility and industrial applications, reducing engineering efforts.
- Cost-effectiveness: Achieving station-wide visibility and streamlined process management at minimal costs.

Solution:

Advantech ECU-579 serves as the core of the system, complying with the IEC 61850-3 standard and providing unparalleled flexibility throughout the substation's lifecycle. To enhance its capabilities, our customer developed modular software, enabling the virtualization of the digital substation control and protection device. This empowers a single device to handle multiple protection relays, simplifying the network and supporting optimal asset management.

Benefits:

- Cost Savings: Reduced device and maintenance costs through centralized protection and control.
- Network Simplicity: Minimized complexity by consolidating protection and control functions.
- Efficient Process Management: Streamlined process management with comprehensive stationwide visibility.
- Flexibility and Scalability: Fast, easy, and cost-effective substation system upgrades to meet evolving network protection requirements.
- Support for Digitalization: Designed to support the increasing digitalization of substations.





citor Base Functionality











Motor







Arc flash



ECU-579









ECU-579	ECU-479	ECU-4784 Series	ECU-P1522LPE
IEC 61850-3 Virtualization Server	IEC-61850-3 Automation Server	IEC-61850-3 Automation PC	2-Port SFP Ethernet Card with HSR/ PRP Support
2nd Generation Intel® Xeon® Scalable Processors	13th Generation Intel® Core™ processors DEPARCEDIAMA with FCC correction to	• Intel® Xeon® E-2276ML, up to 64G DDR4 ECC	• 2 x SFP (100/ 1000 Mbps HSR/PRP selection by
• 12 x DDR4 RDIMM/LRDIMM with ECC, support up to 768GB	• 2 x DDR4 SODIMM with ECC, support up to 64GB	RAM • Intel® Xeon® E3-1505L v5, up to 32G DDR4 ECC	switch)Wide operating temperature range
• 4 x 2.5" hot-swappable HDD/ SSD, 1 x M.2 2280	• 4 x 2.5" swappable SSD, 1 x M.2 2280 NVMe/	RAM	(-25~70 °C)
NVMe/SATA	SATA	 Intel® 6th Core™ Celeron, i3, i5, i7 Processor up 	 Configuration tool for Windows and Linux
• 2 x hot-swappable PSU (100-240 VDC/VAC)	• 2 x swappable PSU (100-240Vpc/Vac, 48Vpc	to 16G DDR3L RAM	 Support IEEE 1588 PTPv2 standard
• 2 x PCle x16, 1 x PCle x8, 1 x PCle x4 Gen.	optional)	• 8 x Giga LAN, 2 x RS-232, 8 x RS-232/ 422/ 485	
3 slots, 1 x ECU-P slots	• 3 x PCle x4 Gen. 3, 1 x PCle x16 Gen. 4, and	serial ports	
• IPMI 2.0-compliant management	1 x ECU-P slots	• 3 x Display output/ 3 x SATA/ 2 x I/O expansion	
		slots	

Industrial Ethernet Switches













EKI-5528I-MB	EKI-7720G-4FPI	EKI-5629C-EI	EKI-7712G-4FPI	EKI-7428G-4XP	EKI-9226G-20FOI
8FE Managed Ethernet Switch support Modbus/ TCP	16GE PoE + 4G SFP Ports Managed Industrial PoE Switch	8FE+2G Combo Managed Ethernet Switch support EtherNet/IP	8GE PoE and 4G SFP Managed Ethernet Switch	24GE+4 10G SFP L2 Managed PoE Switch	IEC61850-3 20G SFP + 6GE Managed Ethernet Switch
8 x Fast Ethernet RJ-45 (EKI- 5528/I-MB) ports	• 16 x IEEE 802.3af/at PoE ports • Up to 420W power budget	• 8 x Fast Ethernet ports + 2 Gigabit Copper/SFP combo	• 8 x IEEE 802.3 af/at PoE Gigabit ports + 4 SFP ports	• 24 x GbE ports and 4 x 10G SFP ports	Dual Power input and 2 relay output
 Entry-Level Managed Switch 	 SFP socket for easy and 	ports (EKI-5629C/I-EI)	 SFP socket for Easy and 	 0 to 60°C operating 	 Redundancy: Gigabit X-Ring
 IXM function enables fast 	flexible fiber expansion	 Entry-level managed switch 	Flexible Fiber Expansion	temperature range	Pro (ultra high-speed recovery
deployment	 Redundancy: X-Ring Pro (ultra- 	 IXM function enables fast 	 Redundancy: X-Ring Pro (ultra 	Management: SNMP v1/v2c/	time < 20 ms), RSTP/STP
Management: SNMP v1/	high-speed recovery time, <20	deployment	high-speed recovery time < 20	v3, WEB, Telnet, Standard MIB	(802.1w/1D),MSTP
v2c/v3, WEB, Standard MIB,	ms), RSTP/STP (802.1w/1D)	 Provides EtherNet/IP EDS 	ms), RSTP/STP (802.1w/1D)	 IXM function enables f 	 Security: 802.1x (Port-Based,
Private MIB	 IXM function enables fast 	(Electronic Data Sheet) file,	 IXM function enables fast 	deployment	MD5/TLS/TTLS/PEAP
	deployment	AOI (Add-On Instructions)	deployment	 Redundancy: Gigabit X-Ring 	Encryption), HTTPS, SSH and
		file, and FactoryTalk® View	 Security: 802.1x (Port-Based, 	Pro (ultra high-speed recovery	SNMPv3
		faceplate	MD5/TLS/TTLS/PEAP	time < 20 ms), RSTP/STP	Management: SNMP v1/v2c/
		Management: SNMP v1/	Encryption), RADIUS	(802.1w/1D), MSTP	v3, WEB, Telnet, Standard MIB
		v2c/v3, WEB, Standard MIB,			 SFP socket for Easy and
		Private MIB			Flexible Fiber Expansion

Unmanaged Ethernet Switches

Communication Gateways

Industrial Cellular Routers & Gateways











EKI-2525I	EKI-2526M	ECU-1251	ECU-150	ICR-4461
Unmanaged Industrial Ethernet Switch	4FE+2FE SC Multi-mode Unmanaged Ethernet Switch	IEC-61850-3-Compliant Edge Communication Gateway with 2 x LAN, 4 x COM	NXP i.MX8M Quad Core Cortex A53, High-Performance IoT Gateway	Ultra High-Speed 5G Router & Powerful Edge Computing Gateway
 Provides 5/8 Fast Ethernet ports with Auto MDI/MDI-X Supports 10/100 Mbps Auto-Negotiation Provides compact size with DIN-rail/Wall mount, and IP30 metal mechanism Supports redundant 12 ~ 48 Vpc power input and P-Fail relay Supports wide operating temperatures 	 Provides 4 x 10/100 Mbps Ethernet ports with RJ45 connector Provides 2 x 100 Mbps Multi-mode SC type fiber optic port Supports full/half duplex flow control Supports MDI/MDI-X auto crossover Provides Redundant 12 ~ 48 Vpc power input 	 ARM Cortex® A8 800-MHz processor w/ 256 MB of DDR3L RAM 2 x 10/ 100 MB LAN, 4 x RS-232/ 485 serial ports 1 x mini-PCle slot for wireless expansion Wide operating temperature range (-40~70 °C) 	 NXP i.MX8M Quad Core Cortex A53 1.3G CPU DDR4 2GB RAM, 16GB eMMC for system storage 2 x RS-232/485 isolated serial ports 2 x 10/100/1000 Ethernet ports 1 x Mini-PCle for WIFI/Cellular/4G 	 5G NR Cellular Connectivity, Sub-6GHz 3GPP Release 16, Support both NSA and SA modes Quad-core CPU with 1 GB RAM 2 x SIM, eSIM Ready, TPM 2.0 5 x GbE (Optional 4x PoE+ PSE) 24 x GbE+ 4 x 10G SFP L2 Managed PoE Switch

Worldwide Presence



Regional Service and Customization Centers

China Kunshan

Taiwan | Taipei | 886-2-2792-7818

Netherlands Eindhoven

Poland

USA | Milpitas, CA

Worldwide Offices

				~	
$-\Lambda$ ϵ ι		,	~ 10	77	^
Asi	аг	0			
				-	_

Taiwan Taipei & IoT Campus 886-2-2792-7818

China

86-10-6298-4346 86-28-8545-0198 Chengdu 852-2720-5118

Japan

0800-500-1055 81-3-6802-1021 81-949-22-2890

Korea

Singapore

65-6442-1000

Malaysia

60-4-537-9188

Thailand

Vietnam

Indonesia

Australia

India

91-94-4839-7300

Americas

North America

1-949-420-2500 1-888-576-9668

Brazil

São Paulo

Mexico

1-800-467-2415 52-55-6275-2777 Europe

Netherlands

Germany

00800-2426-8080/81

France

33-1-4119-4666

Italy

39-02-9544-961

44-0-191-262-4844

Spain

Madrid 34-91-668-86-76

Sweden

Poland

48-22-31-51-100

Russia

8-800-555-01-50 St. Petersburg 8-812-332-57-27

Czech Republic

420-465-524-421

Ireland

Middle East and Africa

90-224-413-3134



Enabling an Intelligent Planet

www.advantech.com

without prior written permission of the publisher.

